High Speed Doors Albany UltraTough



UNITED STEEL PRODUCTS, INC


33-40 127th Place Flushing NY 11368

P: (718) 478-5330 F: (718) 779-8258 www.UnitedSteelProducts.com

The global leader in

ASSA ABLOY

ASSA ABLOY Entrance Systems



Stong, fast and rugged design

When the going gets tough, you need the Albany UltraTough high-performance door from ASSA ABLOY Entrance Systems. The Albany UltraTough can take a hit and hold up in the most rugged industrial applications, while flimsy conventional doors buckle under conditions.







A lifetime of strength and reliability

Even in the harshest conditions, the Albany UltraTough performs like no other door.

- UltraStrong rubber panel
- Heavy-duty self-supporting steel side frames
- Patented Windlok guide system
- Provides more resiliency against damage, extreme weather and high wind loads of up to 88 mph
- Creates a near airtight seal
- Protects people and materials from exposure to extreme weather and contaminates

The Albany UltraTough meets the demands of any environment with a choice of two drive units: the Springless System and Counterbalance System. Whatever you choose, this door helps reduce energy costs, increases productivity, and creates a better working environment.

Guaranteed to stay tough

The Albany UltraTough is built to withstand accidental impact and remain operational.

- The curtain and breakaway bottom beam can be reset quickly without special tools
- Chemical and corrosion resistant heavy-duty side frames ensure superb durability and performance in harsh environments
- Opening speeds up to 60" per second allow you to increase productivity and decrease energy costs

Albany UltraTough applications

The Albany UltraTough is ideal in automotive, distribution, wastewater management, transportation, parking facilities and more.

Technical information

Opening Speeds

Springless System Opening up to 36" per second (size dependent)
Counterbalanced System 60" per second (size dependent)

Door Dimensions

 Max Height
 30 ft (9,144 mm)

 Max Width
 30 ft (9,144 mm)

 Min Height
 8 ft (2438 mm)

 Min Width
 8 ft (2438 mm)

Safety Features

Photo Eye Standard
TruckGuard Light Curtain 40 Infrared through-beam optical sensors

Door Panel

SBR 2 layers of Styrene Butadiene Rubber (SBR)

with polyester cord center

EPDM Optional MSHA Optional

Static Wind Resistance

Windlock & Guide System 20 psf (88 mph) Wind Gussets 30 psf (110 mph)

Door Components

Springless System

Counterbalanced Systems

Side Frames

Self-supporting, heavy-duty painted steel
Idler

Door Roll

8 5/8" diameter. 188" thick tube
complying with ASTM A513

Bottom Bar

Steel construction
Manual Egress

Direct Drive Unit
100k cycle torsion springs
100k cycle torsion springs
4" diameter, 134"tube
100k cycle torsion springs
100k cycle torsio

Control and Drive System

Input Voltage 208-240 V, 440-480 V, 575-600 V,

3 phase

Motor Up to 3.35-Hp, 3 phase, 60 Hz PLC Controller 1-speed or 2-speed

PLC Controller 1-speed or 2-speed AllStar Optional AllStar-Plus Optional

Protection NEMA 4/12 cUL Listed

We offer various options and actuation devices far all Albany products

Exclusive warranty

The Albany UltraTough has the strength, reliability, and speed that stand the test of time and conditions where no other conventional or high speed door can.

- With the AllStar control system, you receive a 5-year or 1,000,000 cycle limited warranty on all Albany UltraTough drive systems.
- A lifetime warranty on the SBR rubber door panel.
- Two year warranty on all other mechanical and electrical components and 1 year for labor.



Heavy duty construction

Self-supporting structural steel columns and header



Optional TruckGuard safety system

Optional TruckGuard safety system eliminates contact with objects in the doorway




UltraStrong curtain

Thick, 2-layer SBR and high tensile strength rubber panel has a lifetime warranty



Patented continuous Windlock design

Continuous windlock design resists high wind pressures without potential damage in a preakaway condition



Airtight seals

Reliable windlock design produces a near airtight seal for climate control and energy savings in harsh environment.





ASSA ABLOY Entrance Systems





UNITED STEEL PRODUCTS, INC

33-40 127th Place Flushing NY 11368

P: (718) 478-5330 F: (718) 779-8258 www.UnitedSteelProducts.com Follow us:







Please enter ASSA ABLOY Entrance in the channel's search field.